

Amendments to the claims:

1. (currently amended) A circular power saw (10), ~~comprising~~ composed of:
a saw assembly (12) with a housing (14, 16) that encloses a motor and a saw blade (18) configured to be driven by the motor[.];

a footplate (22), whereby wherein the saw assembly (12) is pivotably supported on a swivel arm (36), wherein said saw assembly (12) is pivotable relative to the [[a]] footplate (22) to be such that it is adjustable between a minimum and maximum cutting depth[.];

wherein a handle (24) is ~~fixed~~ rigidly connected to the swivel arm (36) footplate (22) independently from the saw assembly (12), such that the saw assembly has no handle for gripping by a user of said power saw[.];

an overload coupling, wherein the saw assembly (12) is pivotably detachable relative to the footplate via the an overload coupling, and wherein said overload coupling is configured to be automatically fully decouple said saw assembly decoupled from an adjusted cutting depth automatically and instantaneously during sawing if kickback occurs, such that if kickback occurs, the saw assembly (12) accelerates upwardly without footplate (22) lifting away from a work piece and kicks into a position of minimum cutting depth relative to the footplate (22) and relative to the handle (24), whereby the handle remains in its prior position.

2. (previously presented) The circular power saw as recited in Claim 1, wherein the saw assembly (12) is configured to be coupled or decoupled via a force-dependent coupling (44) from the handle (24).

3. (previously presented) The circular power saw as recited in Claim 1, wherein the saw is configured to be handled and guided using only the handle (24), which is connected to a swivel arm (36) pivotable on the footplate (22) in a fixed manner.

4. (original) The circular power saw as recited in Claim 1, wherein the saw assembly (12) is supported on the swivel arm (36) such that the cutting depth is adjustable independently of the handle (24).

5. (currently amended) A circular power saw (10) with a handle, comprising:
~~composed of~~ a saw assembly (12) with a housing (14, 16) that encloses a motor and a saw blade (18) configured to be driven by the motor[.];

a footplate (22), whereby wherein the saw assembly (12) is pivotably supported on a swivel arm (36), wherein said saw assembly (12) is pivotable relative to the [[a]] footplate (22) to be such that it is adjustable between a minimum and maximum cutting depth[.];

an overload coupling (44), wherein each cutting depth position of the saw assembly (12) is releasably lockable in position using the an overload coupling (44), the direction of release being toward the minimum cutting depth independently from the handle, wherein the saw assembly (12) is pivotably detachable relative to the footplate via the overload coupling , and wherein said overload coupling is configured to ~~be automatically~~ fully decouple said saw assembly decoupled from an

adjusted cutting depth automatically and instantaneously during sawing if kickback occurs, such that if kickback occurs, the saw assembly (12) accelerates upwardly without footplate (22) lifting away from a work piece, and wherein said saw assembly has no handle for gripping by an operator of said power saw.

6. (previously presented) The circular power saw as recited in claim 5, wherein the overload coupling (44) is configured as a detent coupling (40, 42) and is located on the side of the protective hood (16) facing away from the axis (20).

7. (currently amended) A circular power saw (10), comprising:

~~composed of~~ a saw assembly (12) with a housing (14, 16) that encloses a motor and a saw blade (18) capable of being driven by the motor[.];

a footplate (22), whereby wherein the saw assembly (12) is pivotably supported on a swivel arm (36), wherein said saw assembly (12) is pivotable relative to the [[a]] footplate (22) to be such that it is adjustable between a minimum and maximum cutting depth[.];

~~wherein~~ a handle (24) rigidly connected is fixed to the swivel arm (36) ~~footplate (22)~~ independently from the saw assembly (12), such that the saw assembly has no handle for gripping by a user of said power saw, wherein the saw assembly (12) is configured to be substantially decoupled from handling forces which act on the saw blade (18) from the handle (24) during sawing, wherein the saw assembly (12) is supported on the swivel arm (36) such that the cutting depth is adjustable independently of the handle (24) and wherein the detent coupling (40, 42)

is composed of a locking piece (40) that is grippable at the rear by a detent piece (42).

8. (previously presented) The circular power saw as recited in Claim 6, wherein the locking piece (40) and the detent piece (42) have matching bearing surfaces (52, 54) that are configured to bear against each other at a certain identical angle extending in the direction of the release force, whereby the angle is selected such that the locking piece (40) and the detent piece (42) automatically come apart when a certain minimum force is applied which moves the saw assembly (12) into the cutting depth position "0".

9. (currently amended) A circular power saw (10), comprising:

~~composed of~~ a saw assembly (12) with a housing (14, 16) that encloses a motor and a saw blade (18) configured to be driven by the motor[[,]];

a footplate (22), whereby wherein the saw assembly (12) is pivotably supported on a swivel arm (36), wherein said saw assembly (12) is pivotable relative to the [[a]] footplate (22) to be such that it is adjustable between a minimum and maximum cutting depth[[,]];

wherein a handle (24) rigidly connected ~~is fixed~~ to the swivel arm (36) ~~footplate (22)~~ independently from the saw assembly (12), such that the saw assembly has no handle for gripping by a user of said power saw, wherein the saw assembly (12) is configured to be substantially decoupled from handling forces which act on the saw blade (18) from the handle (24) during sawing, wherein the

saw assembly (12) is supported on the swivel arm (36) such that the cutting depth is adjustable independently of the handle (24), and wherein the force that releases the detent coupling (44) is defined by a lift spring (48) and a coupling spring (46), so that the release force depends on the cutting depth setting.

10. (previously presented) The circular power saw as recited in claim 1, wherein the saw assembly (12) is configured to be automatically substantially or fully decouplable from handling forces which act on the saw blade (18) from the handle during sawing, wherein the saw assembly (12) is configured to be coupled or decoupled via a force-dependent coupling (44), and wherein the force-dependent coupling (44) is the saw assembly (12) with cutting-depth adjusting means (38, 39, 45), so that, if kickback occurs, the cutting-depth adjusting means (38, 39, 45) are detachable, so that the saw assembly (12) can then move out of the way in a manner that minimizes the cutting depth.